

American Thermal Products

Tel: 408-686-0460 Fax: 408-686-0462 Email: sales@medlandandassociates.com

It's Simply COOL!

DC 172x150x51mm

- Housing: Die-Cast Aluminum
- Blade: Plastic UL 94V-O P.B.T.
- Insulation Resistance: 10M Ohm min, 500VDC between wire and frame
- Dielectric Strength: 5mA max. 500VAC/min between lead and frame
- Operation Temp: -10 °C ~ 70 °C
- Life: at 20°C: Ball Bearing 60,000hr



Specification:

Part Number	Bearing Availability	Rated Voltage (VDC)	Air Flow (CFM)	Speed (RPM)	Static Pressure (mmH ₂ O)	Rated Current (mA)	Power (W)	Noise (dBA)	Weight (g)
FD1751B12W3--30	Ball	12	228.0	3400	20.7	1900	23.0	56.0	792
FD1751B12W5--30			203.0	3000	15.8	1400	16.8	52.0	
FD1751B12W7--30			175.0	2600	11.9	850	10.2	48.0	
FD1751B12W9--30			149.0	2200	9.1	600	7.2	43.0	
FD1751B24W3--30		24	228.0	3400	20.7	870	21.0	56.0	
FD1751B24W5--30			203.0	3000	15.8	650	16.0	52.0	
FD1751B24W7--30			175.0	2600	11.9	440	10.5	48.0	
FD1751B24W9--30			149.0	2200	9.1	300	7.4	43.0	
FD1751B48W3--30		48	228.0	3400	20.7	500	24.0	56.0	
FD1751B48W5--30			203.0	3000	15.8	350	17.0	52.0	
FD1751B48W7--30			175.0	2600	11.9	250	12.0	48.0	
FD1751B48W9--30			149.0	2200	9.1	160	8.0	43.0	

