

American Thermal Products

Tel: 408-686-0460 Fax: 408-686-0462 Email: sales@medlandandassociates.com

It's Simply COOL!

DC 90x90x25mm

- Housing / Blade: Plastic UL 94-O P.B.T.
- Insulation Resistance: 10M Ohm, 500VDC/min between bare wire and frame
- Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
- Operation Temp: -10 °C ~ 70 °C (Humidity 35%-85% RH)
- Lead Wire: UL 1007 #22 AWG
- Weight: 183g



Specification:

Part Number	Bearing Availability	Rated Voltage (VDC)	Air Flow (CFM)	Speed (RPM)	Static Pressure (mmH ₂ O)	Rated Current (mA)	Power (W)	Noise (dBA)	Life Hour (25°C)
FD9232B12W5-R	2 Ball	12	58.7	3,200	6.9	270	3.24	42	80,000
FD9232B12W7-R			73.3	4,000	10.7	490	5.88	47	75,000
FD9232B24W5-R		24	58.7	3,200	6.9	170	4.08	42	80,000
FD9232B24W7-R			73.3	4,000	10.7	260	6.24	47	75,000
FD9232B48W5-R	2 Ball	48	58.7	3,200	6.9	120	5.76	42	80,000
FD9232B48W7-R			73.3	4,000	10.7	210	10.08	47	75,000

